



AC TopSeal®

**Self-Adhered, Granular Surfaced,
Single-Ply, Low Slope Rolled Roofing**

Available Colors:

Black, White, Tan, Brown, Grey and Weatherwood.

AC TopSeal® is an innovative, self-adhered, single-ply, finished rolled roofing product for use on low slope wood decks, such as porches, sheds, utility buildings and accessory buildings.

AC TopSeal® is available in
100 sq. ft. (9.3 sq.m.) rolls, 3' x 33.3' (0.9m x 10.1m).

- AC TopSeal® is a self-adhered, rubberized asphalt rolled roofing product.
- The granular surface helps protect against UV, weathering and physical damage.
- It consists of a proprietary modified asphalt and a tough polyester reinforcing core.
- The rugged construction provides outstanding, long-term performance.
- May be used on new construction or re-roofing.
- It can only be installed on primed Oriented Strand Board (OSB) or primed plywood roof decks (no planked roofs).

EASY INSTALLATION

AC TopSeal® rolled roofing is self adhering for fast, easy installation without hot asphalt, open flames or special equipment. Detailed installation instructions can be found at www.nei-act.com

REQUIREMENTS

The minimum roof slope is 1:12 and the maximum slope is 2:12. The roof must drain freely at all points. All decks require priming.



61 Pine Road, Brentwood, NH 03833
1-800-998-4634 www.nei-act.com